




Inserto ceramico Ceramic insert Inserto cerámico	COD. CODE CÓD.				L (inches)	GPA								GAL/1000 Ft2			
		drop	PSI	GMP		4 MPH	5 MPH	6 MPH	8 MPH	10 MPH	12 MPH	15 MPH	20 MPH	2 MPH	3 MPH	4 MPH	5 MPH
✓	422BX010	UC	30	0.84	83	15.1	12.1	10.1	7.6	6.0	5.0	4.0	3.0	0.69	0.46	0.35	0.28
		UC	40	0.97	95	15.2	12.1	10.1	7.6	6.1	5.1	4.0	3.0	0.70	0.46	0.35	0.28
		UC	50	1.09	113	14.3	11.4	9.5	7.1	5.7	4.8	3.8	2.9	0.65	0.44	0.33	0.26
		XC	70	1.28	150	12.7	10.2	8.5	6.4	5.1	4.2	3.4	2.5	0.58	0.39	0.29	0.23
		XC	90	1.46	173	12.5	10.0	8.3	6.2	5.0	4.2	3.3	2.5	0.57	0.38	0.29	0.23
✓	422BX020	UC	30	1.70	110	22.9	18.3	15.3	11.4	9.2	7.6	6.1	4.6	1.05	0.70	0.53	0.42
		UC	40	1.96	120	24.3	19.4	16.2	12.1	9.7	8.1	6.5	4.9	1.11	0.74	0.56	0.45
		UC	50	2.19	132	24.7	19.7	16.4	12.3	9.9	8.2	6.6	4.9	1.13	0.75	0.57	0.45
		UC	70	2.59	145	26.6	21.3	17.7	13.3	10.6	8.9	7.1	5.3	1.22	0.81	0.61	0.49
		XC	90	2.94	157	27.7	22.2	18.5	13.9	11.1	9.2	7.4	5.5	1.28	0.85	0.64	0.51
✓	422BX025	UC	30	2.02	98	30.6	24.4	20.4	15.3	12.2	10.2	8.1	6.1	1.41	0.94	0.70	0.56
		UC	40	2.34	110	31.6	25.3	21.0	15.8	12.6	10.5	8.4	6.3	1.45	0.97	0.73	0.58
		UC	50	2.61	125	31.1	24.8	20.7	15.5	12.4	10.4	8.3	6.2	1.43	0.95	0.71	0.57
		UC	70	3.09	133	34.5	27.6	23.0	17.3	13.8	11.5	9.2	6.9	1.59	1.06	0.79	0.63
		XC	90	3.51	142	36.7	29.4	24.5	18.4	14.7	12.2	9.8	7.3	1.69	1.12	0.84	0.67
✓	422BX045	UC	30	3.73	114	48.5	38.8	32.4	24.3	19.4	16.2	12.9	9.7	2.23	1.49	1.12	0.89
		UC	40	4.31	116	55.2	44.1	36.8	27.6	22.1	18.4	14.7	11.0	2.53	1.69	1.27	1.01
		UC	50	4.82	125	57.2	45.8	38.2	28.6	22.9	19.1	15.3	11.4	2.63	1.75	1.31	1.05
		UC	70	5.70	135	62.7	50.2	41.8	31.3	25.1	20.9	16.7	12.5	2.88	1.92	1.44	1.15
		UC	90	6.46	142	67.7	54.2	45.1	33.9	27.1	22.6	18.1	13.5	3.10	2.07	1.55	1.24
✗	422BX060	UC	30	4.78	118	60.2	48.1	40.1	30.1	24.1	20.1	16.0	12.0	2.76	1.84	1.38	1.10
		UC	40	5.52	126	65.1	52.1	43.4	32.6	26.0	21.7	17.4	13.0	2.99	1.99	1.49	1.19
		UC	50	6.18	145	63.3	50.6	42.2	31.6	25.3	21.1	16.9	12.7	2.90	1.93	1.45	1.16
		UC	70	7.31	167	65.0	52.0	43.3	32.5	26.0	21.7	17.3	13.0	2.98	1.99	1.49	1.19
		UC	90	8.29	185	66.5	53.2	44.3	33.3	26.6	22.2	17.7	13.3	3.05	2.03	1.53	1.22
✗	422BX080	UC	30	6.69	138	72.1	57.7	48.0	36.0	28.8	24.0	19.2	14.4	3.30	2.20	1.65	1.32
		UC	40	7.72	150	76.4	61.2	51.0	38.2	30.6	25.5	20.4	15.3	3.51	2.34	1.75	1.40
		UC	50	8.63	157	81.7	65.3	54.4	40.8	32.7	27.2	21.8	16.3	3.75	2.50	1.87	1.50
		UC	70	10.21	165	91.9	73.5	61.3	46.0	36.8	30.6	24.5	18.4	4.22	2.81	2.11	1.69
		UC	90	11.58	165	104.2	83.4	69.5	52.1	41.7	34.7	27.8	20.8	4.79	3.19	2.39	1.91